



Characteristics

Model	LAY5-EA Series
Panel cutout diameter	22mm, others on request
Type	Spring Return
Rated voltage	Up to 600V (50-60Hz)
Withstand voltage	2.5kV – 1 minute
Impulse voltage	6kVp
Continuous working life (Mechanical)	100 x 10000
Index protection	IP40 (front face), IP20 (body)
Button colour	Black, Green, Red
Terminal assignment	1 – 2 N.C 3 – 4 N.O
Panel thickness supported	1 – 6mm
Standard compliance	IEC/EN 60947-5-1

Environment	
Storage ambient temperature	-40°C to +70°C
Operating ambient temperature	-25°C to +55°C
Relative humidity	≤98%
Installation category	3
Pollution degree	3
Altitude	≤1000m

PART SKU		
<u>LAY5-EA Series</u>		
LAY5-EA31	Green – N.O	LAY5-EA31-GNO
LAY5-EA42	Red – N.C	LAY5-EA42-RNC
LAY5-EA21	Black – N.O	LAY5-EA21-BNO
**For other configurations, please consult us.		

OPTIONAL		
<u>LAY5 Series</u>		
Contact Elements	Normally Open	LAY5-BE101-NO
Contact Elements	Normally Close	LAY5-BE102-NO
**Other accessories on request through email enquiry		