



Characteristics

Model	LAY5-ED Series (Standard Handle)
Panel cutout diameter	22mm, others on request
Operation mode	2 Position or 3 Position
Type	Stay put or Spring return
Contacts	See SKU for options
Rated voltage	Up to 600V (50-60Hz)
Withstand voltage	2.5kV – 1 minute
Impulse voltage	6kVp
Continuous working life (Mechanical)	100 x 10000
Index protection	IP40 (front face), IP20 (body)
Terminal assignment	1 – 2 N.C 3 – 4 N.O
Panel thickness supported	1 – 6mm
Standard compliance	IEC/EN 60947-5-1

Environment	
Storage ambient temperature	-40°C to +70°C
Operating ambient temperature	-25°C to +55°C
Relative humidity	≤98%
Installation category	3
Pollution degree	3
Altitude	≤1000m

PART SKU			
2 POSITIONS			
N/O+N/C		2 Position stay put	LAY5-ED25-SH2PSP
		2 Position spring return	LAY5-ED45-SH2PSR
3 POSITIONS			
N/O+N/O		3 Position stay put	LAY5-ED33-SH3PSP
		3 Position spring return	LAY5-ED53-SH3PSR
*SH2PSP – Denotes “Standard Handle, 2 position, Stay Put” *Contacts – Removable by unscrewing			