



### Characteristics

Model	LAY5-EJ Series (Long Handle)
Panel cutout diameter	22mm, others on request
Operation mode	2 Position or 3 Position
Type	Stay put or Spring return
Contacts	See Part SKU for options
Rated voltage	Up to 600V (50-60Hz)
Withstand voltage	2.5kV – 1 minute
Impulse voltage	6kVp
Continuous working life (Mechanical)	100 x 10000
Index protection	IP40 (front face), IP20 (body)
Terminal assignment	1 – 2 N.C 3 – 4 N.O
Panel thickness supported	1 – 6mm
Standard compliance	IEC/EN 60947-5-1

<b>Environment</b>	
Storage ambient temperature	-40°C to +70°C
Operating ambient temperature	-25°C to +55°C
Relative humidity	≤98%
Installation category	3
Pollution degree	3
Altitude	≤1000m

<b>PART SKU</b>			
<b><u>2 POSITIONS</u></b>			
N/O+N/C		2 Position stay put	<b>LAY5-EJ25-LH2PSP</b>
		2 Position spring return	<b>LAY5-EJ45-LH2PSR</b>
<b><u>3 POSITIONS</u></b>			
N/O+N/O		3 Position stay put	<b>LAY5-EJ33-LH3PSP</b>
		3 Position spring return	<b>LAY5-EJ53-LH3PSR</b>
<p>*LH2PSP – Denotes “Long Handle, 2 position, Stay Put”            *Contacts – Removable by unscrewing            *Additional Contact elements available</p>			