




### Characteristics

Model	LAY4-ES Series
Panel cutout diameter	22mm, others on request
Operation mode	Turn to release
Type	Mushroom push button
Contacts	See SKU for options
Rated voltage	Up to 600V (50-60Hz)
Withstand voltage	2.5kV – 1 minute
Impulse voltage	6kVp
Continuous working life (Mechanical)	100 x 10000
Index protection	IP65 (front face), IP20 (body)
Terminal assignment	1 – 2 N.C 3 – 4 N.O
Panel thickness supported	1 – 6mm
Standard compliance	IEC/EN 60947-5-1

<b>Environment</b>	
Storage ambient temperature	-40°C to +70°C
Operating ambient temperature	-25°C to +55°C
Relative humidity	≤98%
Installation category	3
Pollution degree	3
Altitude	≤1000m

<b>PART SKU</b>			
<b>Lay4-ES Series</b>			
N/O+N/C		Dia. 30mm, Red	<b>LAY4-ES442-TR30R</b>
		Dia. 40mm, Red	<b>LAY4-ES545-TR40R</b>
		Dia. 60mm, Red	<b>LAY4-ES645-TR60R</b>
<p>* <b>Contact us for custom configurations. (Additional contact elements stackable)</b></p> <p>*TR30R – Denotes “Twist Release, Dia.30mm, Red”</p> <p>*Contacts – Removable by unscrewing</p>			

<b>Optional</b>			
		<p><b>Control Box</b></p> <p>Button box for single hole, IP65 rated, Fits dia.22mm, dia.25mm</p>	<b>XDL7-JB01P-IP652225</b>
N.A	N.A	<p><b>Contact Elements</b></p> <p>Normally Open Normally Close</p>	<p><b>LAY4-BE101-NO</b> <b>LAY4-BE102-NC</b></p>
<p>*IP402225* Denotes “IP65 Rated, dia.22mm, dia.25mm”</p> <p>*Other accessories on request through email enquiry</p>			